

# Micro Converter BiDirectional SDI/HDMI 12G



Now you can convert SDI to HDMI and HDMI to SDI in all SD, HD and Ultra HD formats up to 2160p60! Each conversion direction can be a different SD, HD or Ultra HD video standard, it's like getting two converters in one! The all metal durable design is perfect for live production and broadcast. Plus it's small enough to be hidden and used anywhere. It can be powered from any USB-C socket!

**\$165**

## Connections

### SDI Video Inputs

1

### SDI Video Outputs

Automatically matches the HDMI video input.

### HDMI 2.0 Video Inputs

1 x type A.

### HDMI 2.0 Video Outputs

1 x type A.

### SDI Rates

270Mb, 1.5G, 3G, 6G, 12G.

### Multi Rate Support


Auto detection of SD, HD, 2K, Ultra HD and 4K.

### Updates, Configurations and Power

USB Type-C.

### Reclocking

Yes



## Standards

### SD Video Standards

525i59.94 NTSC, 625i50 PAL

---

**HD Video Standards**

720p50, 720p59.94, 720p60  
1080p23.98, 1080p24, 1080p25,  
1080p29.97, 1080p30, 1080p47.95,  
1080p48, 1080p50, 1080p59.94,  
1080p60  
1080PsF25, 1080PsF29.97, 1080PsF30  
1080i50, 1080i59.94, 1080i60

**2K Video Standards**

2Kp23.98 DCI, 2Kp24 DCI, 2Kp25 DCI,  
2Kp29.97 DCI, 2Kp30 DCI,  
2Kp47.95 DCI, 2Kp48 DCI, 2Kp50 DCI,  
2Kp59.94 DCI, 2Kp60 DCI  
2KPsF25 DCI, 2KPsF29.97 DCI,  
2KPsF30 DCI

**Ultra HD Video Standards**

2160p23.98, 2160p24, 2160p25,  
2160p29.97, 2160p30, 2160p47.95,  
2160p48, 2160p50, 2160p59.94,  
2160p60

**4K Video Standards**

4Kp23.98 DCI, 4Kp24 DCI, 4Kp25 DCI,  
4Kp29.97 DCI, 4Kp30 DCI,  
4Kp47.95 DCI, 4Kp48 DCI, 4Kp50 DCI,  
4Kp59.94 DCI and 4Kp60 DCI.

**SDI Compliance**

SMPTE 259M, SMPTE 292M,  
SMPTE 296M, SMPTE 424M,  
SMPTE 425M, SMPTE 2081-1,  
SMPTE 2081-10, SMPTE 2082-1,  
SMPTE 2082-10, SMPTE 2084  
and SMPTE 2108-1

**SDI Video Rates**

SDI video connections are switchable  
between standard definition, 720p,  
1080i, 1080p, 2K DCI, Ultra HD and  
4K DCI.

**SDI Color Precision**

4:2:2. A 33 point LUT can be loaded  
via the software utility for calibrating  
or improving monitor color.

**SDI Color Space**

YUV

**SDI Auto Switching**

Automatically detects SD, HD, 2K DCI,  
Ultra HD and 4K DCI. Level A and B is  
automatically detected on 3G-SDI  
input and user selectable on 3G-SDI  
output.

**HDMI Video Standards**

525i59.94 NTSC, 625i50 PAL  
720p50, 720p59.94, 720p60  
1080p23.98, 1080p24, 1080p25,  
1080p29.97, 1080p30, 1080p47.95,  
1080p48, 1080p50,  
1080p59.94, 1080p60  
1080i50, 1080i59.94, 1080i60  
2160p23.98, 2160p24, 2160p25,  
2160p29.97, 2160p30, 2160p47.95,  
2160p48, 2160p50,  
2160p59.94, 2160p60  
4Kp23.98 DCI, 4Kp24 DCI, 4Kp25 DCI,  
4Kp29.97 DCI, 4Kp30 DCI,  
4Kp47.95 DCI, 4Kp48 DCI, 4Kp50 DCI,  
4Kp59.94 DCI and 4Kp60 DCI.

**HDMI Color Precision**

4:2:2. A 33 point LUT can be loaded  
via the software utility for calibrating  
or improving monitor color.

**HDMI Color Space**

YUV

---

## Copy Protection

HDMI input is unable to capture from copy protected HDMI sources.  
Always confirm copyright ownership before capture or distribution of content.

---

## Camera Control

Bidirectional signal conversion supports Blackmagic Camera Control and Tally.

---

## Settings Control

Via MacOS™ and Windows™ software utility connected by USB.

---

---

## Operating Systems



Mac 10.15 Catalina,  
Mac 11.1 Big Sur or later.



Windows 10, 64-bit.

---

## Software

Internal software upgrade via USB.

---

## Power Requirements

### Power Consumption

5W max.

### Operational Voltage Range

4.4V to 5.25V DC

---

## Environmental Specifications

### Operating Temperature

0° to 40° C (32° to 104° F)

### Storage Temperature

-20° to 60° C (-4° to 140° F)

### Relative Humidity

0% to 90% non-condensing

---

## Physical Specifications



---

## What's Included

Micro Converter BiDirectional SDI/HDMI 12G

---

## Warranty

3 Year Limited Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2024, all rights reserved. All trademarks are property of their respective owners. MSRP includes duties, but excludes sales tax and shipping costs. This website uses remarketing services to advertise on third party websites to previous visitors to our site. You can opt out at any time by changing cookie settings. [Privacy Policy](#)

Blackmagic Design Authorized Reseller